



**XLT 3255-TS**  
Electric  
Conveyor Oven



PO Box 9090 Wichita, KS 67277-0090  
P: 1-316-943-2751 F: 1-316-943-2769  
[www.xltovens.com](http://www.xltovens.com)

**Simple. Smart.**

## XLT 3255-TS

Electric Conveyor Oven

Are you looking for an affordable solution for your cooking needs?

### XLT 3255-TS

Double Stack



### XLT 3255-TS

Triple Stack



The **XLT-3255-TS** uses vertical streams of hot air from 4 pairs of tapered ducts blowing directly on a stainless conveyor belt. These ducts are configurable and adjustable. This cooks your product evenly and quickly. The cook times are adjusted digitally by the conveyor and temperature controls.





### FEATURES

- The **XLT-3255-TS** is available in three configurations, the single, the double, and the triple stack models.
- The optional front sandwich door is provided to load or unload product for different cook times.
- Both exterior AND INTERIOR exposed surfaces are made of easy cleaning stainless steel.
- **XLT™** ovens are manufactured with pride in the USA under stringent quality standards.
- Replacement parts are readily available nationwide (Grainger®) and through our Fast Parts Program direct from the factory, at a fraction of the cost of our competitors.
- The large removable front panel allows for easy access to oven interior, making cleaning much easier than our competitors' ovens of the same size.
- All **XLT™** ovens are 100% factory tested with a minimum 4-hour burn-in time.
- The conveyors can be set up to move either right-to-left or left-to-right.

The **XLT™** electric ovens are an improved version that bakes as fast as our gas models. All ducts, crumb trays, and the conveyor are readily removable for easy cleaning. An overhead ventilation hood is required. Ovens do not come with a pigtail cord, your electrician will provide. All oven fuses are EXTERNALLY panel-mounted allowing easy troubleshooting. A licensed electrician is required to wire all electric models.



# LAYOUT AND DIMENSIONS



3255E-TS\TS2 & TS2E\TS2E Double and Triple Stack Model Dimensions

## General Information:

Belt Width	Bake Time Range*	Max Temperature	Conveyor Opening Height (Max)	Ship Weight Per Oven
32.0"	4 min – 10 min	550°F	3"	800 lbs.

\* Adjustments can be made for other bake time ranges. Specifications and dimensions are subject to change without notice. Local codes and regulations may also apply.

PO Box 9090  
Wichita, KS 67277-0090

P: 1-316-943-2751  
F: 1-316-943-2769  
www.xltovens.com

**XLT**  
OVENS®  
Simple. Smart.

# SPECIFICATIONS

<b>Model XLT 3255E-TS &amp; TS2-208V</b>			
	<b>One Oven</b>	<b>Double Stack</b>	<b>Triple Stack</b>
Height	43"	63"	68"
Length	95"	95"	95"
Depth	61"	61"	61"
Conveyor Width	32"	32"	32"
Max. Temperature	550°F	550°F	550°F
Weight	850 lbs.	1500 lbs.	2100 lbs
<b>Electrical Requirements</b>			
4 Wire Service – L1, L2, L3, 1 Ground (per oven)			
Volts	208 VAC	208 VAC	208 VAC
Amps Per Oven	85 per phase	85 per phase	85 per phase
Phase	3	3	3
Frequency	60 Hz	60Hz	60 Hz
Power requirement per oven 32 Kw			

<b>Model XLT 3255E-TS &amp; TS2-240V</b>			
	<b>One Oven</b>	<b>Double Stack</b>	<b>Triple Stack</b>
Height	43"	63"	68"
Length	95"	95"	95"
Depth	61"	61"	61"
Conveyor Width	32"	32"	32"
Max. Temperature	550°F	550°F	550°F
Weight	850 lbs.	1500 lbs.	2100 lbs
<b>Electrical Requirements</b>			
4 Wire Service – L1, L2, L3, 1 Ground (per oven)			
Volts	240 VAC	240 VAC	240 VAC
Amps Per Oven	67 per phase	67 per phase	67 per phase
Phase	3	3	3
Frequency	60 Hz	60Hz	60 Hz
Power requirement per oven 32 Kw			

<b>Model XLT 3255E-TSE &amp; TS2E -380V</b>			
	<b>One Oven</b>	<b>Double Stack</b>	<b>Triple Stack</b>
Height	43"	63"	68"
Length	95"	95"	95"
Depth	61"	61"	61"
Conveyor Width	32"	32"	32"
Max. Temperature	550°F	550°F	550°F
Weight	850 lbs.	1500 lbs.	2100 lbs
<b>Electrical Requirements</b>			
5 Wire Service – L1, L2, L3, N, 1 Ground (per oven)			
Volts	380 VAC	380VAC	380 VAC
Amps Per Oven	44.7 per phase	44.7 per phase	44.7 per phase
Phase	3	3	3
Frequency	50 Hz	50Hz	50 Hz
Power requirement per oven 32 Kw			



PO Box 9090 Wichita, KS 67277-0090  
 P: 1-316-943-2751 F: 1-316-943-2769  
[www.xltovens.com](http://www.xltovens.com)

